

POWER CONTROL OPTIONS

- Hydraulic Control
- Variable Frequency Control Traction or Hydraulic
- Polechanger / Two Speed Control
- Single Speed Control

HYDRAULIC SYSTEM CONTROLS

- Hydraulic Over Travel Sequencing
- Hydraulic Homing
- Hydraulic Releveling Control
- Hydraulic Vane Sequence Check (via software)
- Hydraulic Oscillation Control
- Hydraulic Star / Delta Pump Starting Control

DOOR CONTROL OPTIONS

- Manual Doors
- Fully Automatic Doors
- Swing Landing Doors & Power Car Doors
- Park Open Control (software option)
- Door Nudging
- Differential Door Dwell Timings
- Limited Landing Door Reopen

INDICATORS

- Direction Arrows
(collective controls only)
- Lift Overload Indicator
- Out of Service Indicator
- Positions Indicators
- Car Call and Landing Indicators
- Fire Control Indicator
- Arrival Gong Control

Our standard MRL cabinet is made from stainless steel and sized at 2100mm high x 440mm wide x 270mm deep.

This control panel houses the Almega II processor and up to 11kW (24Amp) on the Magnetek drive and 11kW (32Amp) on the Ziehl Abegg 4CS drive.

A new, slimline version is also available with the ALMEGA II processor and the Ziehl Abegg 4CS. With dimensions of 2100mm height x 200mm depth x 250mm width, it utilises serial push and indicator networks to reduce size and installation time.

The ZA 4C drive is mounted within the lift shaft and adjacent to the motor. A zetapad programming tool is fitted into the control panel to program, adjust and interrogate the inverter remotely.

All information is for guidance only, E & OE
©Copyright 2020, Lester Control Systems Ltd,
All rights reserved

Head Office

Unit D 18 Imperial Way
Croydon Surrey CR0 4RR
T: 020 8288 0668 | F: 020 8288 0667

Midlands Office

Units 1-4 Wycliffe Industrial
Park Leicester Road Lutterworth
Leicestershire LE17 4HG
T: 01455 204983 | F: 01455 557780

Glasgow Office

4 Lonmay Place, Panorama Business
Park, Glasgow G33 4ER
T: 0141 771 6171